






































Project _____
 AIA # _____ SIS # _____
 Item # _____ Quantity _____ C.S.I. Section 114000



RACK CAPACITY CHART

For Double Wide Units – Side & End Load Racks

RACK CAPACITY CHART FOR DOUBLE WIDE UNITS – SIDE & END LOAD RACKS

PW2E Proofer / RPW2E Retarder/Proofer				PW2S Proofer / RPW2S Retarder/Proofer			
Dimensions	SINGLE END LOAD	SINGLE SIDE LOAD	DOUBLE SIDE LOAD	Dimensions	SINGLE END LOAD	SINGLE SIDE LOAD	DOUBLE SIDE LOAD
	 Typical Rack Dimensions: 20.38"W x 26.0"D	 Typical Rack Dimensions: 28.38"W x 18.0"D	 Typical Rack Dimensions: 28.38"W x 36.0"D		 Typical Rack Dimensions: 20.38"W x 26.0"D	 Typical Rack Dimensions: 28.38"W x 18.0"D	 Typical Rack Dimensions: 28.38"W x 36.0"D
40.5"D MODELS Interior: 37.8"D x 52.6"W Exterior: 43.3"D x 62.0"W	 2	 3	 1	40.5"D MODELS Interior: 37.8"D x 66.0"W Exterior: 43.3"D x 75.5"W	 3	 4	 2
60.5"D MODELS Interior: 57.8"D x 52.6"W Exterior: 63.3"D x 62.0"W	 4	 4	 2	60.5"D MODELS Interior: 57.8"D x 66.0"W Exterior: 63.3"D x 75.5"W	 6	 6	 2
80.5"D MODELS Interior: 77.8"D x 52.6"W Exterior: 83.3"D x 62.0"W	 5	 6	 2	80.5"D MODELS Interior: 77.8"D x 66.0"W Exterior: 83.3"D x 75.5"W	 8	 8	 4
100.5"D MODELS Interior: 97.8"D x 52.6"W Exterior: 103.3"D x 62.0"W	 6	 8	 3	100.5"D MODELS Interior: 97.8"D x 66.0"W Exterior: 103.3"D x 75.5"W	 9	 10	 4
120.5"D MODELS Interior: 117.8"D x 52.6"W Exterior: 123.3"D x 62.0"W	 8	 10	 3	120.5"D MODELS Interior: 117.8"D x 66.0"W Exterior: 123.3"D x 75.5"W	 12	 12	 6

As continued product improvement is a policy of Baxter, specifications are subject to change without notice.



Approved by _____ Date _____ Approved by _____ Date _____